

HIGH SECURITY ABLOY® EXEC CAM LOCKS


CL100E, CL101E, CL103E, CL104E, CL105E, CL106E, CL107E, CL200E, CL201E, CL202E, CL203E

APPLICATIONS

ABLOY® EXEC Cam Locks are specially designed for demanding high security applications such as parking meters, cash dispensers, vending machines, slot machines, cash/safe deposit lockers, and pay phones.

Cams are available as an accessory, please refer to the ABLOY® CAM LOCKS brochure. In some models left handed operation is available on special request.

DIMENSIONS



MATERIAL AND FINISH

Detainer discs, cylinder drum and end nut of brass. Cam, governor, nut lock washer and hex nut of zinc-plated steel. Cylinder housing of chrome-plated brass. First disc of nickel-plated case-hardened steel. Locks CL105E and CL201E have a cylinder housing of chrome-plated case-hardened steel.

LOCK TYPE		CL100E	CL101E	CL103E	CL104E	CL105E	CL106E	CL107E	CL200E	CL201E	CL202E	CL203E
Overall length	A	37	37	43	33	33	43	33	34.5	34.5	44.5	38.5
Maximum door thickness	B	13.5	13.5	19.5	9.5	9.5	19.5	9.5	9.5	9.5	19.5	13.5
Cam distance	C	22.5	22.5	28.5	18.5	18.5	28.5	18.5	18.5	18.5	28.5	22.5
Key removable in locked position only		x		x	x	x			x	x	x	x
Key removable in locked and unlocked position			x				x	x				
Cam turns		90°/180°	360°	90°/180°	90°/180°	90°/180°	360°	360°	90°/180°	90°/180°	90°/180°	90°/180°
Number of discs		11	11	11	9	9	11	9	9	9	11	11
UNIVERSAL-specification		x	x	x	x	x	x	x				
US-specification									x	x	x	x

HIGH SECURITY ABLOY® EXEC SWITCH LOCKS

EP400E, EP401E, EP402E

APPLICATIONS

ABLOY® EXEC Switch Locks provide key-actuated switching for burglar alarms, control boxes and other high security applications.


EP400E: key removable in NO and NC positions

EP401E: key removable in NC position


EP402E: momentary contact, key removable in NC position

Locks are suitable for panels from 0.5 mm to 22 mm in thickness.

DIMENSIONS



WIRING DIAGRAM



MATERIAL AND FINISH

Cylinder housing of chrome-plated case-hardened steel. First disc of nickel-plated case-hardened steel. Switch actuator and switch holder brackets of moulded plastic. Other parts of brass.

Locks have a CHERRY microswitch, type DG1C-B1AA.

Electrical values: 3A, 125VAC/
2A, 30VDC

Working temperature: -25°C to +85°C
Number of discs: 11


HIGH SECURITY ABLOY® T-HANDLE LOCKS

CL290E – SPRING LOADED LATCH, CL291E – DEADLOCKING LATCH

APPLICATIONS

ABLOY® EXEC T-handle locks are ideal for vending machines and for other locking handle applications. Access can only be gained when the lock is removed. Steel bolt provides maximum resistance against attack by pulling.

DIMENSIONS



MATERIAL AND FINISH

Cylinder housing of chrome-plated steel. Plug face chrome-plated case-hardened steel. First disc of nickel-plated case-hardened steel. Bolt of nickel-plated steel. Key removable in locked position only. Number of discs: 9



Abloy Oy
Wahlforsinkatu 20
P.O. Box 108
FIN-80101 JOENSUU
FINLAND
Tel. +358 13 2501
Fax +358 13 250 2209



ABLOY® is a registered trademark of Abloy Oy.

www.abloy.com

Abloy Oy is an ASSA ABLOY Group company.

The ASSA ABLOY Group is the world's leading manufacturer and supplier of locks and associated products, dedicated to satisfying end user needs for security, safety and convenience.

9312507 2/2000

ABLOY® EXEC HIGH SECURITY CAM LOCKS



The advanced ABLOY® EXEC high security cylinder provides extensive master-keying features and vast number of key combinations. It offers smooth and reliable operation and optimum resistance against physical attack. The ABLOY® system offers maximum key security with restricted, patented key profiles and key security levels.

Abloy Oy

An ASSA ABLOY Group company